

## SECTION 1. IDENTIFICATION OF THE SUBSTANCE OR MIXTURE AND OF THE COMPANY

### 1.1 IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY

**Product name:** SMARTMATERIALS RESIN STANDARD BLACK  
**UFI:** 9610-11YC-V006-0DCQ  
**Product type:** Photopolymerizable resin.

### 1.2 RELEVANT IDENTIFIED USES OF THE SUBSTANCE OR MIXTURE AND USES DISAGREE

**Recommended uses:** Resin for 3D printing. Additive manufacturing. Exclusive professional user use.  
**Uses advised against:** No information available.

### 1.3 IDENTIFICATION OF THE COMPANY

SMART MATERIALS 3D PRINTING SL  
 Polígono Industrial El Retamar · C/ Tomillo 7 – Vial G  
 23680 Alcalá la Real (Jaén) SPAIN  
 ☎ +34 953 041 993  
 📠 +34 953 113 527  
[info@smartmaterials3d.com](mailto:info@smartmaterials3d.com)  
[www.smartmaterials3d.com](http://www.smartmaterials3d.com)

### 1.4 EMERGENCY CONTACT

**Emergency phone:** 112

## SECTION 2. HAZARDS IDENTIFICATION

### 2.1 CLASSIFICATION OF THE SUBSTANCE OR MIXTURE

#### CLP Regulation (EC) No 1272/2008

Classification of this product has been carried out in accordance with CLP Regulation (EC) No 1272/2008

Aquatic Chronic 4: Hazardous to the aquatic environment, long-term hazard, Category 4, H413 Skin Sens. 1B: Sensitisation, skin, Category 1B, H317

### 2.2 LABEL ELEMENTS

#### Symbols / Pictograms:



#### Warning words:

Warning

#### Hazard statements:

Aquatic Chronic 4: H413 – May cause long lasting harmful effects to aquatic life. Skin Sens. 1B: h317 – May cause an allergic skin reaction.

#### Cautionary advice:

P261: Avoid breathing dust/fume/gas/mist/vapours/spray  
 P272: Contaminated work clothing should not be allowed out of the workplace.  
 P273: Avoid release to the environment.  
 P280: Wear protective gloves/protective clothing/eye protection/face protection.  
 P302+P352: IF ON SKIN: Wash with plenty of water.  
 P333+P313: If skin irritation or rash occurs: Get medical advice/attention.  
 P501: Dispose of contents/container in accordance with regulations on hazardous waste or packaging and packaging waste respectively.

#### Supplementary information:

Contains Diphenyl (2,4,6-trimethylbenzoyl) phosphine oxide, pentaerythritol tetraacrylate.  
 UFI: 9610-11YC-V006-0DCQ

## 2.3 OTHER HAZARDS:

Product fails to meet PBT/vPvB criteria

## SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

### 3.1 SUBSTANCE

Non-applicable.

### 3.2 CHEMICAL CHARACTERIZATION: MIXTURES

In accordance with Annex II of Regulation (EC) No 1907/2006, the product contains:

| Chemical name/Classification   |  | Identification  |                              | %                 |
|--|--|-----------------|------------------------------|-------------------|
| <b>Esterification products of 4,4' -isopropylidenediphenol, ethoxylated and 2-methylprop-2-enoic acid</b> <sup>(1)</sup> |  | Self-classified | CAS: 41637-38-1              | <b>85 - 100</b>   |
|  |  |                 | CE: 609-946-4                |                   |
|  |  |                 | Index: Non-applicable        |                   |
|  |  |                 | REACH: 01-2119980659-17-XXXX |                   |
| <b>Pentaerythritol tetraacrylate</b> <sup>(1)</sup>  |  | ATP CLP00       | CAS: 4986-89-4               | <b>3 - 9</b>      |
|  |  |                 | CE: 225-644-1                |                   |
|  |  |                 | Index: 607-122-00-9          |                   |
|  |  |                 | REACH: Non-applicable        |                   |
| <b>Diphenyl (2,4,6-trimethylbenzoyl) phosphine oxide</b> <sup>(1)</sup>  |  | Self-classified | CAS: 75980-60-8              | <b>2 - 2.5</b>    |
|  |  |                 | CE: 278-355-8                |                   |
|  |  |                 | Index: 015-203-00-X          |                   |
|  |  |                 | REACH: 01-2119972295-29-XXXX |                   |
| <b>Cyclohexane</b> <sup>(2)</sup>  |  | ATP CLP00       | CAS: 110-82-7                | <b>0.01 - 0.1</b> |
|  |  |                 | CE: 203-806-2                |                   |
|  |  |                 | Index: 601-017-00-1          |                   |
|  |  |                 | REACH: 01-2119463273-41-XXXX |                   |
| <b>Toluene</b> <sup>(2)</sup>  |  | ATP CLP00       | CAS: 108-88-3                | <b>0.01 - 0.1</b> |
|  |  |                 | CE: 203-625-9                |                   |
|  |  |                 | Index: 601-021-00-3          |                   |
|  |  |                 | REACH: 01-2119471310-51-XXXX |                   |
| <b>Phenol</b> <sup>(2)</sup>   |  | ATP CLP00       | CAS: 108-95-2                | <b>&lt;0.01</b>   |
|  |  |                 | CE: 203-632-7                |                   |
|  |  |                 | Index: 604-001-00-2          |                   |
|  |  |                 | REACH: 01-2119471329-32-XXXX |                   |

<sup>(1)</sup> Substances presenting a health or environmental hazard which meet criteria laid down in Regulation (EU) No. 2015/830

<sup>(2)</sup> Substance with a Union workplace exposure limit

## SECTION 4. FIRST AID MEASURES

### 4.1 DESCRIPTION OF FIRST AID MEASURES

- By eye contact** : In case of irritation caused by the fumes, rinse immediately with plenty of water, also under the eyelids. If symptoms persist, contact your doctor.
- By skin contact** : May produce an allergic reaction on the skin. In case of contact, it is recommended to clean the affected area with water by dragging and with neutral soap. In case of skin changes (itching, redness, rashes, blisters ...), go to a doctor with this Safety Data Sheet.
- By inhalation** : It is a product not classified as dangerous by inhalation, however, in case of symptoms of poisoning it is recommended to remove the affected person from the place of exposure, supply them with clean air and keep them at rest. Seek medical attention if symptoms persist.
- By ingestion** : Do not induce vomiting, if it occurs keep the head tilted forward to avoid aspiration. Keep the patient at rest. Rinse the mouth and throat, as there is a possibility that they have been affected on ingestion.

## 4.2 MOST IMPORTANT SYMPTOMS AND EFFECTS, ACUTE AND DELAYED

Acute and delayed effects are listed in Sections 2 and 11.

## 4.3 INDICATIONS FOR MEDICAL ATTENTION AND SPECIAL TREATMENTS THAT SHOULD BE GIVEN IMMEDIATELY

No hay information available

## SECTION 5. FIREFIGHTING MEASURES

### 5.1 EXTINGUISHING MEDIA

**Suitable extinguishing media** : Non-flammable product under normal conditions of storage, handling and use, containing flammable substances. In case of ignition as a consequence of handling, storage or improper use, preferably use multipurpose powder extinguishers (ABC powder), in accordance with the Regulation of fire protection installations (R.D. 513/2017 and subsequent modifications).

**Unsuitable extinguishing media** : It is recommended not to use full jet water as an extinguishing agent.

### 5.2 SPECIAL HAZARDS ARISING FROM THE SUBSTANCE OR MIXTURE

Because of combustion or thermal decomposition, reaction by-products are generated that can be highly toxic and, consequently, can present a high risk to health.

### 5.3 ADVICE FOR FIREFIGHTER

**Instructions** : No fighting instruction is required.

**Special protective equipment for firefighters** : As in any fire, wear MSHA / NIOSH pressure-demand self-contained breathing apparatus (approved or equivalent) and all necessary protective equipment.

## SECTION 6. ACCIDENTAL RELEASE MEASURES

### 6.1 PERSONAL PRECAUTIONS, PROTECTIVE EQUIPMENT AND EMERGENCY PROCEDURES

**For personnel who are not part of the emergency services** : Isolate leaks if it does not pose an additional risk to persons performing this function. Evacuate the area and keep unprotected people away. In the event of potential contact with the spilled product, the use of personal protection elements is mandatory (see SECTION 8). Avoid as a priority the formation of flammable vapor-air mixtures, either through ventilation or the use of an inerting agent. Remove any source of ignition. Eliminate electrostatic charges by interconnecting all conductive surfaces on which static electricity can form, while the assembly is grounded.

**For emergency personnel** : Wear with appropriate personal protective equipment (see SECTION 8).

### 6.2 ENVIRONMENTAL PRECAUTIONS

Avoid at all costs any type of spillage into the aquatic environment. Adequately contain the absorbed / collected product in hermetically sealable containers. Notify the competent authority in the event of exposure to the public or the environment.

### 6.3 METHODS AND MATERIAL FOR CONTAINMENT AND CLEANING

It is recommended:

Absorb spillage with sand or inert absorbent and move to a safe place. Do not absorb in sawdust or other combustible absorbents. For any consideration regarding disposal, consult SECTION 13.

## SECTION 7. HANDLING AND STORAGE

### 7.1 PRECAUTIONS FOR SAFE HANDLING

**General precautions**

: Comply with current legislation on the prevention of occupational hazards. Keep containers tightly closed. Control spills and residues, eliminating them with safe methods (SECTION 6). Avoid free spillage from container. Maintain order and cleanliness where dangerous products are handled.

**Technical recommendations for the prevention of fires and explosions**

: Avoid evaporation of the product as it contains flammable substances, which can form flammable vapor / air mixtures in the presence of ignition sources. Control ignition sources (mobile phones, sparks ...) and transfer at slow speeds to avoid the generation of electrostatic charges. Consult SECTION 10 on conditions and materials to avoid.

**Technical recommendations to prevent ergonomic and toxicological hazards**

: For exposure control consult SECTION 8. Do not eat, drink, or smoke in work areas; wash hands after each use, and remove contaminated clothing and protective equipment before entering eating areas.

**Technical recommendations to prevent environmental risks**

: Due to the danger of this product for the environment, it is recommended to handle it within an area that has pollution control barriers in case of spillage, as well as to have absorbent material in the vicinity of it.

### 7.2 CONDITIONS FOR SAFE STORAGE, INCLUDING ANY INCOMPATIBILITIES

**Requirements for the warehouse and containers**

: Store in a dry place, protect from sunlight, store between 5°C and 30°C.

**Rules for joint storage**

: Not necessary.

**Additional information on storage conditions**

: Store in tightly closed containers in a cool, dry place.

## SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

### 8.1 CONTROL PARAMETERS

Substances whose occupational exposure limits have to be monitored in the workplace (European OEL, not country-specific legislation):

Directive (EU) 2000/39, Directive 2004/37/EC, Directive (EU) 2006/15, Directive (EU) 2009/161, Directive (EU) 2017/164, Directive (EU) 2019/1831:

| Identification                                    |  | Occupational exposure limits |         |                       |
|---|--|------------------------------|---------|-----------------------|
| <b>Cyclohexane</b><br>CAS: 110-82-7 CE: 203-806-2 |  | IOELV (8h)                   | 200 ppm | 700 mg/m <sup>3</sup> |
|   |  | IOELV (STEL)                 | -       | -                     |
| <b>Toluene</b><br>CAS: 108-88-3 CE: 203-625-9     |  | IOELV (8h)                   | 50 ppm  | 192 mg/m <sup>3</sup> |
|   |  | IOELV (STEL)                 | 100 ppm | 384 mg/m <sup>3</sup> |
| <b>Phenol</b><br>CAS: 108-95-2 CE: 203-632-7      |  | IOELV (8h)                   | 2 ppm   | 8 mg/m <sup>3</sup>   |
|   |  | IOELV (STEL)                 | 4 ppm   | 16 mg/m <sup>3</sup>  |

**DNEL (Workers):**

| Identification   |            | Short exposure |                | Long exposure           |                |
|--|------------|----------------|----------------|-------------------------|----------------|
|  |            | Systemic       | Local          | Systemic                | Local          |
| Esterification products of 4,4' - isopropylidenediphenol, ethoxylated and 2-methylprop-2enoic acid<br>CAS: 41637-38-1<br>CE: 608-946-4 | Oral       | Non-applicable | Non-applicable | Non-applicable          | Non-applicable |
|  | Dermal     | Non-applicable | Non-applicable | 2 mg/ Kg                | Non-applicable |
|  | Inhalation | Non-applicable | Non-applicable | 3,52 mg/ m <sup>3</sup> | Non-applicable |

|  |            |                         |                         |                          |                        |
|--|------------|-------------------------|-------------------------|--------------------------|------------------------|
| Diphenyl(2,4,6-trimethylbenzoyl) phosphine oxide<br>CAS: 75980-60-8<br>CE: 278-355-8 | Oral       | Non-applicable          | Non-applicable          | Non-applicable           | Non-applicable         |
|  | Dermal     | Non-applicable          | Non-applicable          | 0,233 mg/ Kg             | Non-applicable         |
|  | Inhalation | Non-applicable          | Non-applicable          | 0,822 mg/ m <sup>3</sup> | Non-applicable         |
| Cyclohexane<br>CAS: 110-82-7<br>CE: 203-806-2  | Oral       | Non-applicable          | Non-applicable          | Non-applicable           | Non-applicable         |
|  | Dermal     | Non-applicable          | Non-applicable          | 2016 mg/ Kg              | Non-applicable         |
|  | Inhalation | 1400 mg/ m <sup>3</sup> | 1400 mg/ m <sup>3</sup> | 700 mg/ m <sup>3</sup>   | 700 mg/ m <sup>3</sup> |
| Toluene<br>CAS: 108-88-33<br>CE: 203-625-9   | Oral       | Non-applicable          | Non-applicable          | Non-applicable           | Non-applicable         |
|  | Dermal     | Non-applicable          | Non-applicable          | 384 mg/ Kg               | Non-applicable         |
|  | Inhalation | 384 mg/ m <sup>3</sup>  | 384 mg/ m <sup>3</sup>  | 192 mg/ m <sup>3</sup>   | 192 mg/ m <sup>3</sup> |
| Phenol<br>CAS: 108-95-2<br>CE: 203-632-7   | Oral       | Non-applicable          | Non-applicable          | Non-applicable           | Non-applicable         |
|  | Dermal     | Non-applicable          | Non-applicable          | 1,23 mg/ Kg              | Non-applicable         |
|  | Inhalation | Non-applicable          | 16 mg/ m <sup>3</sup>   | 8 mg/ m <sup>3</sup>     | Non-applicable         |

### DNEL (General population):

| Identification   |            | Short exposure         |                        | Long exposure            |                         |
|--|------------|------------------------|------------------------|--------------------------|-------------------------|
|  |            | Systemic               | Local                  | Systemic                 | Local                   |
| Esterification products of 4,4' - isopropylidenediphenol, ethoxylated and 2-methylprop-2enoic acid<br>CAS: 41637-38-1<br>CE: 608-946-4 | Oral       | Non-applicable         | Non-applicable         | 0,5 mg/ Kg               | Non-applicable          |
|  | Dermal     | Non-applicable         | Non-applicable         | 1 mg/ Kg                 | Non-applicable          |
|  | Inhalation | Non-applicable         | Non-applicable         | 0,87 mg/ m <sup>3</sup>  | Non-applicable          |
| Diphenyl(2,4,6-trimethylbenzoyl) phosphine oxide<br>CAS: 75980-60-8<br>CE: 278-355-8   | Oral       | Non-applicable         | Non-applicable         | 0,0833 mg/ Kg            | Non-applicable          |
|  | Dermal     | Non-applicable         | Non-applicable         | 0,0833 mg/ Kg            | Non-applicable          |
|  | Inhalation | Non-applicable         | Non-applicable         | 0,145 mg/ m <sup>3</sup> | Non-applicable          |
| Cyclohexane<br>CAS: 110-82-7<br>CE: 203-806-2  | Oral       | Non-applicable         | Non-applicable         | 59,4 mg/ Kg              | Non-applicable          |
|  | Dermal     | Non-applicable         | Non-applicable         | 1186 mg/ Kg              | Non-applicable          |
|  | Inhalation | 412 mg/ m <sup>3</sup> | 412 mg/ m <sup>3</sup> | 206 mg/ m <sup>3</sup>   | 206 mg/ m <sup>3</sup>  |
| Toluene<br>CAS: 108-88-33<br>CE: 203-625-9   | Oral       | Non-applicable         | Non-applicable         | 8,13 mg/ Kg              | Non-applicable          |
|  | Dermal     | Non-applicable         | Non-applicable         | 226 mg/ Kg               | Non-applicable          |
|  | Inhalation | 226 mg/ m <sup>3</sup> | 226 mg/ m <sup>3</sup> | 56,5 mg/ m <sup>3</sup>  | 56,5 mg/ m <sup>3</sup> |
| Phenol<br>CAS: 108-95-2<br>CE: 203-632-7   | Oral       | Non-applicable         | Non-applicable         | 0,4 mg/ Kg               | Non-applicable          |
|  | Dermal     | Non-applicable         | Non-applicable         | 0,4 mg/ Kg               | Non-applicable          |
|  | Inhalation | Non-applicable         | Non-applicable         | 1,32 mg/ m <sup>3</sup>  | Non-applicable          |

### PNEC:

| Identification   |              |                |                         |              |
|--|--------------|----------------|-------------------------|--------------|
| Diphenyl(2,4,6-trimethylbenzoyl) phosphine oxide<br>CAS: 75980-60-8<br>CE: 278-355-8 | STP          | Non-applicable | Water                   | 0.0014 mg/L  |
|  | Soil         | 0,0222 mg/Kg   | Marine water            | 0,00014 mg/L |
|  | Intermittent | 0,014 mg/L     | Sediment (Water)        | 0.115 mg/kg  |
|  | Oral         | Non-applicable | Sediment (Marine water) | 0.0115 mg/kg |
| Cyclohexane<br>CAS: 110-82-7<br>CE: 203-806-2  | STP          | 3.24 mg/L      | Water                   | 0.207 mg/L   |
|  | Soil         | 3.38 mg/kg     | Marine water            | 0.207 mg/L   |
|  | Intermittent | 0.207 mg/L     | Sediment (Water)        | 16.68 mg/Kg  |
|  | Oral         | Non-applicable | Sediment (Marine water) | 6.68 mg/Kg   |
| Toluene<br>CAS: 108-88-33<br>CE: 203-625-9   | STP          | 13.61 mg/L     | Water                   | 0.68 mg/L    |
|  | Soil         | 2.89 mg/kg     | Marine water            | 0.68 mg/L    |
|  | Intermittent | 0.68 mg/L      | Sediment (Water)        | 16.39 mg/kg  |
|  | Oral         | Non-applicable | Sediment (Marine water) | 16.39 mg/kg  |

|  |              |                |                         |             |
|--|--------------|----------------|-------------------------|-------------|
| Phenol<br>CAS: 108-95-2<br>CE: 203-632-7 | STP          | 2.1 mg/L       | Water                   | 0.008 mg/L  |
|  | Soil         | 0.136 mg/kg    | Marine water            | 0.008 mg/L  |
|  | Intermittent | 0.031 mg/L     | Sediment (Water)        | 0.091 mg/kg |
|  | Oral         | Non-applicable | Sediment (Marine water) | 0.009 mg/kg |





## 8.2 EXPOSURE CONTROL

### A.- Individual protection measures, such as personal protective equipment



As a preventive measure, the use of basic personal protective equipment is recommended, with the corresponding CE marking in accordance with R.D. 1407/1992 and subsequent modifications. For more information on personal protective equipment (storage, use, cleaning, maintenance, protection class ...) consult the information leaflet provided by the PPE manufacturer. The indications contained in this point refer to the pure product. The protection measures for the diluted product may vary depending on its degree of dilution, use, application method, etc. To determine the obligation to install emergency showers and / or eyewashes in warehouses, the regulations regarding the storage of chemical products applicable in each case will be taken into account. For more information see sections 7.1 and 7.2.

All the information included here is a recommendation, and it is necessary to specify it by the occupational risk prevention services as it is not aware of the additional prevention measures that the company may have or if they have been included in the relevant risk assessment.

### B.- Respiratory protection



| Pictogram   | PPE   | Labelling   | CEN Standard        | Observations   |
|---|---|---|---------------------|--|
| <br>Mandatory respiratory tract protection | Self-filtering mask for gases and vapours (Filter type: FFP2) |  | EN 405:2002+A1:2010 | Replace when the odor or taste of the contaminant is detected inside the mask or face adapter. When the pollutant does not have good warning properties, the use of insulating equipment is recommended. |
| <br>Mandatory respiratory tract protection | Self-filtering mask for gases and vapors (Filter type: A)     |  | EN 405:2002+A1:2010 | Replace when the odor or taste of the contaminant is detected inside the mask or face adapter. When the pollutant does not have good warning properties, the use of insulating equipment is recommended. |

### C.- Specific protection for the hands


| Pictogram  | PPE   | Labelling   | CEN Standard   | Observations  |
|--|---|---|--|---|
| <br>Mandatory hand protection | Protective gloves against minor risks (Material: Nitrile) |  | EN 420:2004<br>A1:2010<br>EN ISO 374-1:2016<br>A1:2018 | Replace the gloves at any sign of deterioration. For prolonged periods of exposure to the product for professional / industrial users, the use of CE III gloves is recommended. |

Since the product is a mixture of different materials, the resistance of the glove material cannot be calculated in advance with complete reliability and therefore must be checked before application.



**D.- Ocular and facial protection**

| Pictogram  | PPE   | Labelling   | CEN Standard                    | Observations  |
|--|---|---|---------------------------------|---|
| <br>Mandatory face protection | Goggles against splashes and / or projections |  | EN 166:2002<br>EN ISO 4007:2018 | Clean daily and disinfect periodically according to the manufacturer's instructions. Its use is recommended in case of risk of splashing. |

**E.- Body protection**

| Pictogram | PPE                  | Labelling   | CEN Standard  | Observations  |
|-----------|----------------------|---|---|---|
|           | Work clothing        |  | EN ISO 6529:2013,<br>EN ISO 6530:2005,<br>EN ISO 13688:2013,<br>EN 464:1994 | Replace before any indication of deterioration. For prolonged periods of exposure to the product for professional / industrial users CE III is recommended. |
|           | Anti-slip work shoes |  | EN ISO 20347:2012   | Replace before any indication of deterioration. For prolonged periods of exposure to the product for professional / industrial users CE III is recommended, |

**E.- Additional emergency measures**

| Emergency measure   | Standards                                       | Emergency measure  | Standards                                      |
|---|---|--|--|
| <br>Emergency shower | ANSI Z358-1<br>ISO 3864-1:2011, ISO 3864-4:2011 | <br>Eyewash stations | DIN 12 899<br>ISO 3864-1:2011, ISO 3864-4:2011 |

**Environmental exposure controls:**

Under Community environmental protection legislation, it is recommended to avoid spilling both the product and its packaging into the environment. For additional information see section 7.1.D

**Volatile organic compounds:**

In application to R.D. 117/2003 and subsequent modifications (Directive 2010/75 / EU), this product has the following characteristics:

|                           |                                   |
|---------------------------|-----------------------------------|
| V.O.C (Supply):           | 0,18 % weight                     |
| V.O.C DENSITY at 20 °C:   | 2,04 kg/m <sup>3</sup> (2,04 g/L) |
| Average carbon number:    | 6,5                               |
| Average molecular weight: | 88,15 g/mol                       |

**SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**
**9.1 INFORMATION ON BASIC PHYSICAL AND CHEMICAL PROPERTIES**

|                       |           |
|-----------------------|-----------|
| <b>Physical state</b> | : Liquid  |
| <b>Appearance</b>     | : Viscous |
| <b>Colour</b>         | : Black   |
| <b>Odour</b>          | : Resin   |



|                                    |                            |
|------------------------------------|----------------------------|
| <b>Density</b>                     | : 1.125 g/cm <sup>3</sup>  |
| <b>Kinematic viscosity at 40°C</b> | : <20,5 mm <sup>2</sup> /s |
| <b>pH</b>                          | : 6 – 8 (at 100%)          |
| <b>Flash point</b>                 | : Non-flammable (>60°C)    |
| <b>Autoignition temperature</b>    | : 260 °C                   |

## 9.2 OTHER INFORMATION

Non available

## SECTION 10. STABILITY AND REACTIVITY

### 10.1 REACTIVITY

None are expected under normal use conditions.

### 10.2 CHEMICAL STABILITY

Stable under recommended storage conditions.

### 10.3 POSSIBILITY OF HAZARDOUS REACTIONS

None are expected under normal use conditions.

### 10.4 CONDITIONS TO AVOID

Caution against overheating. Caution against sunlight. Prolonged exposure will cause product degradation.

### 10.5 INCOMPATIBLE MATERIALS

Avoid strong acids.  
Avoid alkalis or strong bases.

### 10.6 HAZARDOUS DECOMPOSITION PRODUCTS

See SECTION 5.2

## SECTION 11. TOXICOLOGICAL INFORMATION

### 11.1 INFORMATION ON TOXICOLOGICAL EFFECTS

There are no experimental data on the product itself regarding toxicological properties.

#### **Dangerous effects for health:**

In case of repetitive or prolonged exposure or at concentrations higher than those established by the occupational exposure limits, adverse health effects may occur depending on the route of exposure:

#### A- Ingestion (acute effect):

- Acute toxicity: Based on available data, the classification criteria are not met, however, it contains substances classified as dangerous for ingestion. For more information see SECTION 3.
- Corrosivity / Irritability: Based on available data, the classification criteria are not met, however, it contains substances classified as dangerous for this effect. For more information see SECTION 3.

#### B- Inhalation (acute effect):

- Acute toxicity: Based on available data, the classification criteria are not met, however, it contains substances classified as dangerous by Inhalation. For more information see SECTION 3.
- Corrosivity / Irritability: Based on available data, the classification criteria are not met, however, it contains substances classified as dangerous for this effect. For more information see SECTION 3.

#### C- Contact with skin and eyes (acute effect):



- Contact with the skin: Based on the available data, the classification criteria are not met, however, it contains substances classified as dangerous for contact with the skin. For more information see SECTION 3.
- Eye contact: Based on available data, the classification criteria are not met, however it does contain substances classified as dangerous for this effect. For more information see SECTION 3.

D- CMR effects (carcinogenicity, mutagenicity y toxicity for reproduction):

- Carcinogenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for the effects described. For more information see SECTION 3. IARC: Toluene (3); Phenol (3); Carbon black (2B).
- Mutagenicity: Based on available data, the classification criteria are not met, however, it contains substances classified as dangerous with mutagenic effects. For more information see SECTION 3.
- Reproductive toxicity: Based on available data, the classification criteria are not met, however, it contains substances classified as dangerous for this effect. For more information see SECTION 3.

E- Sensitizing effect:

- Respiratory: Based on the available data, the classification criteria are not met, as it does not contain substances classified as dangerous with sensitizing effects above the limits set forth in point 3.2 of Regulation (EC) 2015/830. For more information see sections 2, 3 and 15.

Dermal: Prolonged contact with the skin can lead to PPE sodium from allergic contact dermatitis.

F- Specific Target Organ Toxicity (STOT)-single exposure:

Based on available data, the classification criteria are not met, however, it does contain substances classified as dangerous by Inhalation. For more information see SECTION 3.

G- Specific target organ toxicity (STOT)-repeated exposure:

- Specific target organ toxicity (STOT) -repeated exposure: Based on available data, the classification criteria are not met, however, it contains substances classified as dangerous by repetitive exposure. For more information see SECTION 3.
- Skin: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see SECTION 3.

H- Aspiration hazard:

Based on available data, the classification criteria are not met, however, it does contain substances classified as dangerous for this effect. For more information see SECTION 3.

**Specific toxicological information of the substances:**

| Identification   | Acute toxicity  |                 | Genus  |
|--|-----------------|-----------------|--------|
| Diphenyl(2,4,6-trimethylbenzoyl) phosphine oxide<br>CAS: 75980-60-8<br>CE: 278-355-8 | DL50 oral       | 5500 mg/kg      | Rat    |
|  | DL50 Dermal     | Non-applicable  |        |
|  | DL50 Inhalation | Non-applicable  |        |
| Cyclohexane<br>CAS: 110-82-7<br>CE: 203-806-2  | DL50 oral       | 5100 mg/Kg      | Rat    |
|  | DL50 Dermal     | Non-applicable  |        |
|  | DL50 Inhalation | Non-applicable  |        |
| Toluene<br>CAS: 108-88-33<br>CE: 203-625-9   | DL50 oral       | 5580 mg/Kg      | Rat    |
|  | DL50 Dermal     | 12124 mg/Kg     | Rat    |
|  | DL50 Inhalation | 28,1 mg/L (4 h) | Rat    |
| Phenol<br>CAS: 108-95-2<br>CE: 203-632-7   | DL50 oral       | 100 mg/Kg       | Rat    |
|  | DL50 Dermal     | 630 mg/Kg       | Rabbit |
|  | DL50 Inhalation | Non-applicable  |        |

## SECTION 12. ECOLOGICAL INFORMATION

### 12.1 TOXICITY

| Identification   | Acute toxicity |                  | Species                 | Genus      |
|--|----------------|------------------|-------------------------|------------|
| Diphenyl(2,4,6-trimethylbenzoyl) phosphine oxide<br>CAS: 75980-60-8<br>CE: 278-355-8 | LC50           | >1 – 10 (96 h)   |                         | Fish       |
|  | EC50           | >1 – 10 (48 h)   |                         | Crustacean |
|  | EC50           | >1 – 10 (72 h)   |                         | Algae      |
| Cyclohexane<br>CAS: 110-82-7<br>CE: 203-806-2  | LC50           | >1 – 10 (96 h)   |                         | Fish       |
|  | EC50           | >1 – 10 (48 h)   |                         | Crustacean |
|  | EC50           | >1 – 10 (72 h)   |                         | Algae      |
| Toluene<br>CAS: 108-88-33<br>CE: 203-625-9   | LC50           | 13 mg/L (96 h)   | Carassius auratus       | Fish       |
|  | EC50           | 11.5 mg/L (48 h) | Daphnia magna           | Crustacean |
|  | EC50           | 125 mg/L (48 h)  | Scenedesmus subspicatus | Algae      |
| Phenol<br>CAS: 108-95-2<br>CE: 203-632-7   | LC50           | 14 mg/L (96 h)   | Leuciscus idus          | Fish       |
|  | EC50           | 12 mg/L (24 h)   | Daphnia magna           | Crustacean |
|  | EC50           | 370 mg/L (96 h)  | Chlorella vulgaris      | Algae      |

### 12.2 PERSISTENCE AND DEGRADABILITY

| Identification                                | Degradability |                | Biodegradability |          |
|---|---------------|----------------|------------------|----------|
| Cyclohexane<br>CAS: 110-82-7<br>CE: 203-806-2 | BOD5          | Non-applicable | Concentration    | 100 mg/L |
|   | COD           | Non-applicable | Period           | 28 días  |
|   | BOD5/COD      | Non-applicable | % Biodegradable  | 0 %      |
| Toluene<br>CAS: 108-88-33<br>CE: 203-625-9    | BOD5          | 2,5 g O2/g     | Concentration    | 100 mg/L |
|   | COD           | Non-applicable | Period           | 14 días  |
|   | BOD5/COD      | Non-applicable | % Biodegradable  | 100 %    |
| Phenol<br>CAS: 108-95-2<br>CE: 203-632-7      | BOD5          | 1,68 g O2/g    | Concentration    | 100 mg/L |
|   | COD           | 2,33 g O2/g    | Period           | 14 días  |
|   | BOD5/COD      | 0,72           | % Biodegradable  | 85 %     |

### 12.3 BIOACCUMULATIVE POTENTIAL

| Identification                                | Bioaccumulation potential |          |
|---|---------------------------|----------|
| Cyclohexane<br>CAS: 110-82-7<br>CE: 203-806-2 | BCF                       | 66       |
|   | Pow Log                   | 3,44     |
|   | Potential                 | Moderate |
| Toluene<br>CAS: 108-88-33<br>CE: 203-625-9    | BCF                       | 13       |
|   | Pow Log                   | 2,73     |
|   | Potential                 | Low      |
| Phenol<br>CAS: 108-95-2<br>CE: 203-632-7      | BCF                       | 17       |
|   | Pow Log                   | 1,48     |
|   | Potential                 | Low      |

### 12.4 MOBILITY IN SOIL

| Identification                                | Absorption/Desorption |                | Volatility |          |
|---|-----------------------|----------------|------------|----------|
| Cyclohexane<br>CAS: 110-82-7<br>CE: 203-806-2 | Koc                   | Non-applicable | Henry      | 100 mg/L |
|   | Conclusion            | Non-applicable | Dry soil   | 28 días  |
|   | Surface tension       | Non-applicable | Moist soil | 0 %      |
| Toluene<br>CAS: 108-88-33<br>CE: 203-625-9    | Koc                   | 2,5 g O2/g     | Henry      | 100 mg/L |
|   | Conclusion            | Non-applicable | Dry soil   | 14 días  |
|   | Surface tension       | Non-applicable | Moist soil | 100 %    |

|  |                        |                          |                   |          |
|--|------------------------|--------------------------|-------------------|----------|
| Phenol<br>CAS: 108-95-2<br>CE: 203-632-7 | <b>Koc</b>             | 1,68 g O <sub>2</sub> /g | <b>Henry</b>      | 100 mg/L |
|  | <b>Conclusion</b>      | 2,33 g O <sub>2</sub> /g | <b>Dry soil</b>   | 14 días  |
|  | <b>Surface tension</b> | 0,72                     | <b>Moist soil</b> | 85 %     |

## 12.5 RESULTS OF PBT AND vPvB ASSESSMENT

Non-applicable

## 12.6 OTHERS ADVERSE EFFECTS

No information available

## SECTION 13. DISPOSAL CONSIDERATIONS

### 13.1 WASTE TREATMENT METHODS

| Code      | Description   | Waste class (Regulation (EU) n° 1357/2014) |
|-----------|---|--|
| 20 01 27* | Paint, inks, adhesives and resins containing hazardous substances | Dangerous                                  |

#### Type of waste (Regulation (UE) n° 1357/2014):

HP14 Ecotoxic

#### Waste management (disposal and evaluation):

Consult the authorized waste manager for recovery and disposal operations in accordance with Annex 1 and Annex 2 (Directive 2008/98 / EC, Law 22/2011). According to codes 15 01 (2014/955 / EU), if the container has been in direct contact with the product, it will be managed in the same way as the product itself, otherwise it will be managed as non-hazardous waste. Dumping into water courses is discouraged. See section 6.2.

#### Legislative provisions related to waste management:

In accordance with Annex II of Regulation (EC) No. 1907/2006 (REACH), the community or state provisions related to waste management are included.

Community legislation: Directive 2008/98 / EC, 2014/955 / EU, Regulation (EU) No. 1357/2014

National legislation: Law 22/2011, Royal Decree 180/2015, Law 11/1997

## SECTION 14. TRANSPORT INFORMATION

|             |                |
|-------------|----------------|
| <b>ADR</b>  | : No regulated |
| <b>RID</b>  | : No regulated |
| <b>IATA</b> | : No regulated |
| <b>IMDG</b> | : No regulated |

## SECTION 15. REGULATORY INFORMATION

### 15.1 SAFETY, HEALTH AND ENVIRONMENTAL STANDARDS / LEGISLATION SPECIFIC TO THE SUBSTANCE OF THE MIXTURE

Candidate substances for authorization in Regulation (EC) 1907/2006 (REACH): Non-applicable

Substances included in Annex XIV of REACH (authorization list) and expiration date: non-applicable

Regulation (EC) 1005/2009, on substances that deplete the ozone layer: non-applicable

Active substances which have been included in Article 95 of Regulation (EU) No. 528/2012: Non-applicable

REGULATION (EU) No 649/2012, relative to the export and import of dangerous chemical products: non-applicable

**Seveso III:**

Non-applicable

**Restrictions on the marketing and use of certain dangerous substances and mixtures (Annex XVII of the REACH regulation, etc. ...):**

Shall not be used in:

- Decorative items intended to produce lighting or colour effects obtained through different phases, for example, ambient lamps and ashtrays,
- Fun and joke articles,
- Games for one or more participants or any item that is going to be used as such, even with a decorative character.

Occupational exposure to respirable crystalline silica must be controlled in accordance with Directive (EU) 2019/130.

**Specific provisions regarding the protection of people or the environment:**

It is recommended to use the information collected in this safety data sheet as input data in a risk assessment of local circumstances to establish the necessary risk prevention measures for the handling, use, storage and disposal of this product.

**Other legislation:**

Regulation (EC) No. 1272/2008 of the European Parliament and of the Council, of December 16, 2008, on classification, labelling and packaging of substances and mixtures, and which modifies and repeals Directives 67/548 / EEC and 1999 / 45 / EC and Regulation (EC) No. 1907/2006 and all its subsequent amendments are amended.

## 15.2 CHEMICAL SAFETY ASSESSMENT

The supplier has not carried out evaluation of chemical safety.

## SECTION 16. OTHER INFORMATION

**Legislation applicable to safety data sheets:**

This safety data sheet has been developed in accordance with ANNEX II-Guide for the preparation of Safety Data Sheets of Regulation (CE) No. 1907/2006 (Regulation (EU) No. 2015/830)

**Modifications with respect to the previous safety data sheet that affect risk management measures:**

Non-applicable

**Texts of the legislative phrases contemplated in SECTION 2:**

H413: May be harmful to aquatic life with long lasting effects.

H317: May cause an allergic skin reaction.

**Texts of the legislative phrases contemplated in SECTION 3:**

The phrases indicated do not refer to the product itself, they are for information only and refer to the individual components that appear in SECTION 3

**Regulation nº1272/2008 (CLP):**

Acute Tox. 3: H301 + H311 + H331 - Toxic if swallowed, in contact with skin or Inhalation.

Aquatic Acute 1: H400 - Very toxic to aquatic organisms.

Aquatic Chronic 1: H410 - Very toxic to aquatic life with long lasting effects.

Aquatic Chronic 2: H411 - Toxic to aquatic life with long lasting effects.  
Aquatic Chronic 4: H413 - May be harmful to aquatic life with long lasting effects.  
Asp. Tox. 1: H304 - May be fatal if swallowed and enters airways.  
Eye Irrit. 2: H319 - Causes serious eye irritation.  
Flam. Liq. 2: H225 - Highly flammable liquid and vapor.  
Mutates. 2: H341 - Suspected of causing genetic defects.  
Repr. 2: H361d - Suspected of damaging the fetus.  
Repr. 2: H361f - Suspected of damaging fertility.  
Skin Corr. 1B: H314 - Causes severe skin burns and eye damage.  
Skin Irrit. 2: H315 - Causes Dermal irritation.  
Skin Sens. 1: H317 - May cause an allergic skin reaction.  
Skin Sens. 1B: H317 - May cause an allergic skin reaction.  
STOT RE 2: H373 - May cause damage to organs through prolonged or repeated exposure.  
STOT SE 3: H336 - May cause drowsiness or dizziness.

**Classification procedure:**

Aquatic Chronic 4: Calculation method  
Skin Sens. 1B: Calculation method

**Advice regarding training:**

Minimum training in occupational risk prevention is recommended for the personnel who are going to handle this product, to facilitate the understanding and interpretation of this safety data sheet, as well as the labeling of the product.

**Main bibliographic sources:**

<http://echa.europa.eu>  
<http://eur-lex.europa.eu>

**Abbreviations and acronyms:**

ADR: European Agreement on the International Transport of Dangerous Goods by Road  
IMDG: International Maritime Dangerous Goods Code  
IATA: International Air Transport Association  
ICAO: International Civil Aviation Organization  
COD: Chemical Oxygen Demand  
BOD5: Biological Oxygen Demand at 5 days  
BCF: Bioconcentration Factor  
LD50: Lethal Dose 50  
LC50: Lethal Concentration 50  
EC50: Effective Concentration 50  
Log POW: Logarithm Octanol Water Partition Coefficient  
Koc: Organic Carbon Partition Coefficient  
SDS: Safety Data Sheet  
UFI: unique formula identifier  
IARC: International Agency for Research on Cancer

The data that can be extracted from this safety data sheet is based on the current state of our knowledge, this information should be treated as a guide for transport, safe storage, and handling. The information provided does not constitute any guarantee of the product's qualities. Furthermore, it is the user's responsibility to handle the product in accordance with local regulations and standards.

**The information provided in this security sheet does not generate any contractual legal relationship.**